


EXTERNAL SKIVE Balfit® 2 Wire Braid & 4 Spiral Ferrule



20.200.

REFERENCE	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.200.04	- 4	6,3	1/4"	20.0	30.6
20.200.05	- 5	8,0	5/16"	24.0	30.0
20.200.06	- 6	9,5	3/8"	25.0	32.0
20.200.08	- 8	12,7	1/2"	30.0	34.0
20.200.10	- 10	16,0	5/8"	34.0	37.0
20.200.12	- 12	19,0	3/4"	38.0	43.0
20.200.16	- 16	25,4	1"	36.4	50.0
20.200.20	- 20	32,0	1,1/4"	56.0	59.0
20.200.24	- 24	38,0	1,1/2"	62.0	63.1
20.200.32	- 32	50,8	2"	75.1	78.0


MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

VERSIONS: stainless steel AISI 316

Suitable to be used on medium and high pressure braided and 4 spiral hoses:
FORZA DUE; FORZA DUE "SHARK SKIN"; FORZA DUE "TROPIC; BALMASTER BESTFLEX 4SP;
2-MAX; 3-MAX; BALWASH 1W; BALWASH 2W

DOUBLE SKIVE Balfit® 4 Spiral Ferrule



20.405.

REFERENCE	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.405.20	- 20	31,8	1,1/4"	88.0	55.0
20.405.24	- 24	38,1	1,1/2"	94.0	62.0
20.405.32	- 32	50,8	2"	99.0	78.0

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

VERSIONS: stainless steel AISI 316

Suitable to be used on high pressure 4 spiral hoses:
POWERSPIR BESTFLEX 4SH