




# NON SKIVE Balfit® 1 & 2 Wire Braid Ferrule



20.204. / 20.302.

REFERENCE	hose dash	hose Ø		dimensions (mm)	
		mm	inch	L	D
20.204.03	- 3	4,8	3/16"	26.0	21.0
20.302.04	- 4	6,3	1/4"	25.8	22.0
20.302.05	- 5	8,0	5/16"	27.4	24.0
20.302.06	- 6	9,5	3/8"	30.0	26.0
20.302.08	- 8	12,7	1/2"	32.5	30.0
20.302.10	- 10	16,0	5/8"	35.0	34.0
20.302.12	- 12	19,0	3/4"	40.0	38.0
20.204.16	- 16	25,4	1"	47.6	46.3
20.204.20	- 20	32,0	1-1/4"	55.0	58.0
20.204.24	- 24	38,0	1-1/2"	60.3	65.0
20.204.32	- 32	50,8	2"	62.7	78.0
20.204.40	- 40	63,0	2-1/2"	72.2	95.0
20.204.48	- 48	76,0	3"	80.0	110.0

**MATERIAL:** Carbon Steel

**FINISH:** Chromium-(VI) Free plating / **VERSIONS:** stainless steel AISI 316  
ROHS compliant

## Suitable to be used on medium and high pressure braided hoses:

FORZA UNO; FORZA UNO "SHARK SKIN"; FORZA UNO "TROPIC"; FORZA DUE; FORZA DUE "SHARK SKIN"; FORZA DUE "TROPIC"; BALPAC PREMIUM; BALPAC PREMIUM "SHARK SKIN"; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000; BALPAC 3000 "SHARK SKIN"; 2-MAX JACK; BALWASH 1W; BALWASH 2W