
Balflex®

Interlock Male NPTF Pipe (AGN)

26.0400.

SAE J516 / SAE J476A



	hose	hose Ø	thread	C Cut Off	нех
REFERENCE	dash	inch	inch	mm	mm
26.0400.1212	-12	3/4"	3/4" - 14	36.0	27
26.0400.1616	-16	1"	1" - 11.1/2	46.0	36
26.0400.2020	-20	1.1/4"	1.1/4" - 11.1/2	50.7	46
26.0400.2424	-24	1.1/2"	1.1/2" - 11.1/2	50.5	50
26.0400.3232	-32	2"	2" - 11.1/2	57.5	65

MATERIAL: Carbon Steel


ROHS compliant

FINISH: Chromium-(VI) Free plating / VERSIONS: Stainless Steel (add an 'S' ROHS compliant at the end of the REFERENCE)

Interlock Female **ORFS Swivel**

26.4414.

ISO 12151-1 / ISO 8434-3 / SAE J516



	hose	hose Ø	thread	C Cut Off	HEX
REFERENCE	dash	inch	inch	mm	mm
26.4414.1212	-12	3/4"	1.3/16" - 14	29.0	36
26.4414.1616	-16	1"	1.7/16" - 12	31.6	41
26.4414.2020	-20	1.1/4"	1.11/16" – 12	31.5	50
26.4414.2424	-24	1.1/2"	2" - 12	33.7	50

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating / VERSIONS: Stainless Steel (add an 'S' at the end of the REFERENCE)