


Interlock 45° Swept Female **BSP Parallel Pipe with** O-ring Swivel (DKOR 45°)



26.3142.


ISO 12151-6 / ISO 8434-6 / BS 5200

	hose	hose Ø	thread	C Cut Off	н	НЕХ
REFERENCE	dash	inch	inch	mm	mm	mm
26.3142.1212	-12	3/4"	3/4" - 14	67.6	28.3	32
26.3142.1616	-16	1"	1" - 11	80.7	33.8	38
26.3142.2020	-20	1.1/4"	1.1/4" – 11	94.5	37.5	50
26.3142.2424	-24	1.1/2"	1.1/2" - 11	116.5	49.2	55
26.3142.3232	-32	2"	2" - 11	136.5	59.6	70

MATERIAL: Carbon Steel VERSIONS: Stainless Steel (ad: FINISH: Chromium-(VI) Free plating / at the end of the REFERENCE) ROHS compliant

VERSIONS: Stainless Steel (add an 'S' **NOTES:** On larger sizes nuts can be at the end of the REFERENCE) supplied with Trust-Wire Nut (W)

Interlock 90° Swept Female **BSP Parallel Pipe with** O-ring Swivel (DKOR 90°)



26.3192.

ISO 12151-6 / ISO 8434-6 / BS 5200

	hose	hose Ø	thread	C Cut Off	н	HEX
REFERENCE	dash	inch	inch	mm	mm	mm
26.3192.1212	-12	3/4"	3/4" - 14	57.0	55.0	32
26.3192.1616	-16	1"	1" - 11	73.0	71.0	38
26.3192.2020	-20	1.1/4"	1.1/4" - 11	87.0	77.0	50
26.3192.2424	-24	1.1/2"	1.1/2" - 11	105.0	100.0	55
26.3192.3232	-32	2"	2" - 11	135.0	128.0	70

MATERIAL: Carbon Steel FINISH: Chromium-(VI) Free plating / at the end of the REFERENCE) ROHS compliant

VERSIONS: Stainless Steel (add an 'S' NOTES: On larger sizes nuts can be

supplied with Trust-Wire Nut (W)