

HOSESHIELD XT PROTECTIVE SLEEVE



Hydraulic and industrial hose protection sleeve – 11.400

Nylon black colour, US MSHA IC-252/02 approval.

REFERENCE	#	I.D. inch	flat width inch	thickness inch	length ft
HS-017	11.400.017	0.67	1.18	0.03	164
HS-020	11.400.020	0.79	1.42	0.03	164
HS-023	11.400.023	0.91	1.57	0.03	164
HS-025	11.400.025	0.98	1.69	0.03	164
HS-027	11.400.027	1.06	1.77	0.03	164
HS-031	11.400.031	1.22	2.05	0.03	164
HS-033	11.400.033	1.30	2.17	0.03	164
HS-036	11.400.036	1.42	2.36	0.03	164
HS-040	11.400.040	1.57	2.60	0.03	164
HS-044	11.400.044	1.73	2.91	0.03	164
HS-047	11.400.047	1.85	3.03	0.03	164
HS-053	11.400.053	2.09	3.39	0.03	164
HS-055	11.400.055	2.17	3.54	0.03	164
HS-060	11.400.060	2.36	3.86	0.03	164
HS-066	11.400.066	2.60	4.17	0.03	164
HS-073	11.400.073	2.87	4.65	0.03	164
HS-078	11.400.078	3.07	4.96	0.03	164
HS-085	11.400.085	3.35	5.35	0.03	164
HS-093	11.400.093	3.66	5.91	0.03	164
HS-112	11.400.112	4.41	7.01	0.03	164

CONSTRUCTION: 100% high tensile Nylon 6 Multifilament Yarn into a high tenacity braid

THICKNESS: 0.031 inch thick overlapping layers of synthetic Nylon 6 Yarn with 840 denier yarn

ABRASION RESISTANCE: according to ISO 6945, for more than 50 000 cycles

STRETCHING BREAK: up to 33 to 43%

TEMPERATURE: -40°C (-40°F) / +120°C (+248°F)