

JETWASH MICROLINE LIGHT



12.160W.04

High pressure Thermoplastic Jet washing and lubrication hose

REFERENCE	#	inch	SAE Dash	ID mm	OD mm	MPa PSI	MPa PSI	MIN BEND RAD mm	KG kg/m
JETW-04	12.160W.04	1/4"	-4	6,4	12,5	16,0 2400	64,0 9600	100	0,10

INNER TUBE: polyethylene tube resistant to water, grease and oil
REINFORCEMENT: 2 high tensile polyester

OUTER TUBE: black PVC compound resistant to abrasion and weather
SAFETY FACTOR: 4:1

APPLICATION: hobby type jet washing and lubricators
TEMPERATURE RANGE: -40°C (-40°F) +100°C (+212°F)

COUPLINGS: Balflex® 2-piece fittings serie 23 with 20 serie ferrules

BALFLEX JETWASH MICRO LINE - DN6 - 1/4" - WP 16 MPa / 2320 PSI - DATE

JET CLEAN



10.1039.

High pressure, 2 aramidic braids reinforced thermoplastic sewer jet cleaning hose

REFERENCE	#	inch	SAE Dash	ID mm	OD mm	MPa PSI	MPa PSI	MIN BEND RAD mm	KG kg/m
JC-08	10.1039.08	1/2"	-8	12,7	22,5	24,1 3500	60,3 8750	100	0,21
JC-10	10.1039.10	5/8"	-10	16,0	25,6	20,7 3000	51,8 7500	115	0,35
JC-12	10.1039.12	3/4"	-12	19,0	29,2	20,7 3000	51,8 7500	125	0,48
JC-16	10.1039.16	1"	-16	25,4	37,5	20,7 3000	51,8 7500	160	0,58
JC-20	10.1039.20	1.1/4"	-20	31,8	46,5	20,7 3000	51,8 7500	250	0,65

INNER TUBE: internal core in polyester
REINFORCEMENT: 2 high tensile aramidic fiber braids

OUTER TUBE: orange polyurethane high abrasion resistance
SAFETY FACTOR: 2.5:1

APPLICATION: sewer cleaning with high pressure water
TEMPERATURE RANGE: -40°C (-40°F) +65°C (+149°F)

COUPLINGS: Balflex® 2-piece fittings serie 23 with 20 serie ferrules

BALFLEX JET CLEAN - DN12 - 1/2" - WP 24.1 MPa / 3500 PSI - DATE