




Female ORFS Swivel 45° Elbow- OFT45



BF21.4444.

ISO 12151-1 / ISO 8434-3 / SAE J1453

REFERENCE	#	hose		thread	dimensions		
		dash	inch		C - Cut Off	H	HEX
BF2104-04OF45	BF21.4444.0404	04	1/4"	9/16"-18	35	10	17
BF2104-06OF45	BF21.4444.0406	04	1/4"	11/16"-18	35	11	22
BF2106-04OF45	BF21.4444.0604	06	3/8"	9/16"-18	40	15	17
BF2106-06OF45	BF21.4444.0606	06	3/8"	11/16"-18	40	13,5	22
BF2106-08OF45	BF21.4444.0608	06	3/8"	13/16"-16	40	15	24
BF2108-06OF45	BF21.4444.0806	08	1/2"	11/16"-18	46	18,5	24
BF2108-08OF45	BF21.4444.0808	08	1/2"	13/16"-16	43	15	24
BF2108-10OF45	BF21.4444.0810	08	1/2"	1"-14	45	16	30
BF2108-12OF45	BF21.4444.0812	08	1/2"	1.3/16"-12	54	21	36
BF2110-10OF45	BF21.4444.1010	10	5/8"	1"-14	50	18	30
BF2110-12OF45	BF21.4444.1012	10	5/8"	1.3/16"-12	55	21	36
BF2112-12OF45	BF21.4444.1212	12	3/4"	1.3/16"-12	65	21	36
BF2112-16OF45	BF21.4444.1216	12	3/4"	1.7/16"-12	74	25	41
BF2116-12OF45	BF21.4444.1612	16	1"	1.3/16"-12	75	25	36
BF2116-16OF45	BF21.4444.1616	16	1"	1.7/16"-12	76	25	41

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

Suitable to be used on medium and high pressure braided hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN; FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN; BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W