
Balflex[©]

Female ORFS Swivel 90° Elbow - OFT90



BF21.4494.

ISO 12151-1 / ISO 8434-3 / SAE J1453

		hose		thread	dimensions		
REFERENCE	#	dash	inch		C - Cut Off	н	HEX
BF2104-040F90	BF21.4494.0404	04	1/4"	9/16"-18	33,0	21,0	17
BF2104-060F90	BF21.4494.0406	04	1/4"	11/16"-18	33,0	23,0	22
BF2106-040F90	BF21.4494.0604	06	1/4"	9/16"-18	34,5	27,0	17
BF2106-060F90	BF21.4494.0606	06	3/8"	11/16"-18	34,5	29,0	22
BF2106-080F90	BF21.4494.0608	06	3/8"	13/16"-16	37,0	30,0	24
BF2108-060F90	BF21.4494.0806	08	1/2"	11/16"-18	39,5	34,0	22
BF2108-080F90	BF21.4494.0808	08	1/2"	13/16"-16	39,5	35,0	24
BF2108-100F90	BF21.4494.0810	08	1/2"	1"-14	39,5	36,5	30
BF2108-120F90	BF21.4494.0812	08	1/2"	1.3/16"-12	42,0	45,0	36
BF2110-080F90	BF21.4494.1008	10	5/8"	13/16"-16	45,0	30,0	24
BF2110-100F90	BF21.4494.1010	10	5/8"	1"-14	54,0	40,0	30
BF2110-120F90	BF21.4494.1012	10	5/8"	1.3/16"-12	54,0	48,0	36
BF2112-120F90	BF21.4494.1212	12	3/4"	1.3/16"-12	57,0	48,0	36
BF2112-160F90	BF21.4494.1216	12	3/4"	1.7/16"-12	57,0	56,0	41
BF2116-120F90	BF21.4494.1612	16	1"	1.3/16"-12	65,0	58,0	36
BF2116-160F90	BF21.4494.1616	16	1"	1.7/16"-12	70,0	60,0	41

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating / ROHS compliant

Suitable to be used on medium and high pressure braided hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SĤARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN; FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN; BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W

36 www.balflex.com

Balflex assumes no liability for typographical errors or other errors. For any precise technical information you must always contact our technical department. Dimensions and Data shown may be changed without notice.