




Female JIC 37° Swivel - FJ



BF21.4H12.

ISO 12151-5 / ISO 8434-2 / SAE J516 / SAE J514

REFERENCE	#	hose		thread	dimensions		
		dash	inch		C - Cut Off	W	HEX
BF2104-04FJ	BF21.4H12.0404	04	1/4"	7/16"-20	22,7	14	14
BF2104-05FJ	BF21.4H12.0405	04	1/4"	1/2"-20	22,7	14	16
BF2104-06FJ	BF21.4H12.0406	04	3/8"	9/16"-18	24,7	14	19
BF2106-04FJ	BF21.4H12.0604	06	3/8"	7/16"-20	20,2	17	14
BF2106-06FJ	BF21.4H12.0606	06	3/8"	9/16"-18	20,7	17	19
BF2106-08FJ	BF21.4H12.0608	06	3/8"	3/4"-16	26,0	19	22
BF2106-10FJ	BF21.4H12.0610	06	3/8"	7/8"-14	28,5	22	27
BF2108-06FJ	BF21.4H12.0806	08	1/2"	9/16"-18	25,0	22	19
BF2108-08FJ	BF21.4H12.0808	08	1/2"	3/4"-16	27,0	22	22
BF2108-10FJ	BF21.4H12.0810	08	1/2"	7/8"-14	30,0	22	27
BF2108-12FJ	BF21.4H12.0812	08	1/2"	1.1/16"-12	34,0	25	32
BF2110-08FJ	BF21.4H12.1008	10	5/8"	3/4"-16	28,5	22	22
BF2110-10FJ	BF21.4H12.1010	10	5/8"	7/8"-14	30,5	22	27
BF2110-12FJ	BF21.4H12.1012	10	5/8"	1.1/16"-12	35,5	27	32
BF2112-10FJ	BF21.4H12.1210	12	3/4"	7/8"-14	33,3	27	27
BF2112-12FJ	BF21.4H12.1212	12	3/4"	1.1/16"-12	34,8	27	32
BF2112-14FJ	BF21.4H12.1214	12	3/4"	1.3/16"-12	36,3	32	38
BF2112-16FJ	BF21.4H12.1216	12	3/4"	1.5/16"-12	36,3	32	38
BF2116-12FJ	BF21.4H12.1612	16	1"	1.3/16"-12	34,2	32	32
BF2116-16FJ	BF21.4H12.1616	16	1"	1.5/16"-12	35,7	32	38

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

Suitable to be used on medium and high pressure braided hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN; FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN; BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W