


Male NPTF Pipe Rigid - MP



BW23.0400.

SAE J516 / SAE J514

REFERENCE	#	hose		thread	dimensions	
		dash	inch		C - Cut Off	HEX
BW2304-02MP	BW23.0400.0402	04	1/4"	1/8"-27	24,2	12
BW2304-04MP	BW23.0400.0404	04	1/4"	1/4"-18	29,7	14
BW2304-06MP	BW23.0400.0406	04	1/4"	3/8"-18	30,7	17
BW2304-08MP	BW23.0400.0408	04	1/4"	1/2"-14	35,7	22
BW2306-04MP	BW23.0400.0604	06	3/8"	1/4"-18	27,2	17
BW2306-06MP	BW23.0400.0606	06	3/8"	3/8"-18	28,7	19
BW2306-08MP	BW23.0400.0608	06	3/8"	1/2"-14	33,7	22
BW2308-04MP	BW23.0400.0804	08	1/2"	1/4"-18	31,0	19
BW2308-06MP	BW23.0400.0806	08	1/2"	3/8"-18	31,5	19
BW2308-08MP	BW23.0400.0808	08	1/2"	1/2"-14	35,5	22
BW2308-12MP	BW23.0400.0812	08	1/2"	3/4"-14	38,0	27
BW2310-08MP	BW23.0400.1008	10	5/8"	1/2"-14	37,5	22
BW2310-12MP	BW23.0400.1012	10	5/8"	3/4"-14	40,0	27
BW2312-08MP	BW23.0400.1208	12	3/4"	1/2"-14	38,8	27
BW2312-12MP	BW23.0400.1212	12	3/4"	3/4"-14	39,3	27
BW2312-16MP	BW23.0400.1216	12	3/4"	1"-11.5	45,8	36
BW2316-12MP	BW23.0400.1612	16	1"	3/4"-14	40,7	32
BW2316-16MP	BW23.0400.1616	16	1"	1"-11.5	46,2	36
BW2316-20MP	BW23.0400.1620	16	1"	1.1/4" - 11.5	49,2	46
BW2320-20MP	BW23.0400.2020	20	1.1/4"	1.1/4" - 11	49,5	46
BW2320-24MP	BW23.0400.2024	20	1.1/4"	1.1/2" - 11	52,5	50
BW2324-24MP	BW23.0400.2424	24	1.1/2"	1.1/2" - 11	52,4	50
BW2324-32MP	BW23.0400.2432	24	1.1/2"	2" - 11	58,4	65
BW2332-32MP	BW23.0400.3232	32	2"	2" - 11	57,9	65

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating / ROHS compliant

Suitable to be used on medium and high pressure braided and spiral hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN; FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN; BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W; BALMASTER BESTFLEX R12; BALMASTER BESTFLEX 4SP; POWERSPIR BESTFLEX 4SH; POWERSPIR BESTFLEX R13 (3/4" & 1"); POWERSPIR BESTFLEX R15 (3/4" & 1")