


Male NPTF Swivel 90° Elbow - MPX90



BW23.0490.

SAE J516 / SAE J514

REFERENCE	#	hose		thread	dimensions			
		dash	inch		C - Cut Off	H	W	HEX
BW2304-02MPX90	BW23.0490.0402	04	1/4"	1/8"-27	22,7	40,1	17	17
BW2304-04MPX90	BW23.0490.0404	04	1/4"	1/4"-18	22,7	40,1	17	17
BW2304-06MPX90	BW23.0490.0406	04	1/4"	3/8"-18	22,7	39,3	17	19
BW2306-04MPX90	BW23.0490.0604	06	3/8"	1/4"-18	21,0	40,9	17	17
BW2306-06MPX90	BW23.0490.0606	06	3/8"	3/8"-18	21,0	38,5	17	19
BW2306-08MPX90	BW23.0490.0608	06	3/8"	1/2"-14	23,5	40,1	24	22
BW2308-06MPX90	BW23.0490.0806	08	1/2"	3/8"-18	26,5	41,0	22	19
BW2308-08MPX90	BW23.0490.0808	08	1/2"	1/2"-14	26,5	47,0	22	22
BW2312-12MPX90	BW23.0490.1212	12	3/4"	3/4"-14	28,8	49,7	27	32
BW2316-16MPX90	BW23.0490.1616	16	1"	1"-11.5	42,7	60,0	32	38

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating /
ROHS compliant

Suitable to be used on medium and high pressure braided and spiral hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN;
FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN;
BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM
TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK
SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W; BALMASTER BESTFLEX R12;
BALMASTER BESTFLEX 4SP; POWERSPIR BESTFLEX 4SH; POWERSPIR BESTFLEX R13 (3/4" &
1"); POWERSPIR BESTFLEX R15 (3/4" & 1")