


# Female ORFS Swivel 45° Elbow- OFT45



BW23.4444.

ISO 12151-1 / ISO 8434-3 / SAE J1453

REFERENCE	#	hose		thread	dimensions		
		dash	inch		C - Cut Off	H	HEX
BW2304-04OF45	BW23.4444.0404	04	1/4"	9/16"-18	35	10	17
BW2304-06OF45	BW23.4444.0406	04	1/4"	11/16"-16	35	11	22
BW2306-04OF45	BW23.4444.0604	06	3/8"	9/16"-18	40	15	17
BW2306-06OF45	BW23.4444.0606	06	3/8"	11/16"-16	40	13,5	22
BW2306-08OF45	BW23.4444.0608	06	3/8"	13/16"-16	40	15	24
BW2308-06OF45	BW23.4444.0806	08	1/2"	11/16"-16	46	18,5	24
BW2308-08OF45	BW23.4444.0808	08	1/2"	13/16"-16	43	15	24
BW2308-10OF45	BW23.4444.0810	08	1/2"	1"-14	45	16	30
BW2308-12OF45	BW23.4444.0812	08	1/2"	1.3/16"-12	54	21	36
BW2310-10OF45	BW23.4444.1010	10	5/8"	1"-14	50	18	30
BW2310-12OF45	BW23.4444.1012	10	5/8"	1.3/16"-12	55	21	36
BW2312-12OF45	BW23.4444.1212	12	3/4"	1.3/16"-12	65	21	36
BW2312-16OF45	BW23.4444.1216	12	3/4"	1.7/16"-12	74	25	41
BW2316-12OF45	BW23.4444.1612	16	1"	1.3/16"-12	75	25	36
BW2316-16OF45	BW23.4444.1616	16	1"	1.7/16"-12	76	25	41
BW2316-20OF45	BW23.4444.1620	16	1"	1.11/16"-12	81	33	50
BW2320-20OF45	BW23.4444.2020	20	1.1/4"	1.11/16"-12	94	32	50
BW2320-24OF45	BW23.4444.2024	20	1.1/4"	2"-12	102	38	60
BW2324-24OF45	BW23.4444.2424	24	1.1/2"	2"-12	123	44	60

**MATERIAL:** Carbon Steel

**FINISH:** Chromium-(VI) Free plating /  
ROHS compliant

## Suitable to be used on medium and high pressure braided and spiral hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN;  
FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN;  
BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM  
TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK  
SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W; BALMASTER BESTFLEX R12;  
BALMASTER BESTFLEX 4SP; POWERSPIR BESTFLEX 4SH; POWERSPIR BESTFLEX R13 (3/4" &  
1"); POWERSPIR BESTFLEX R15 (3/4" & 1")