
Balflex®

45° Elbow SAE 3000 PSI Code 61 Flange - PA45



BW23.7043.

SAE J516 (CODE 61) / SAE J518 / ISO 12151-3

		hose		flange size	dimensions		
REFERENCE	#	dash	inch		C - Cut Off	Н	D
BW2308-08PA45	BW23.7043.0808	08	1/2"	1/2"	57,0	23,0	30,2
BW2308-12PA45	BW23.7043.0812	08	1/2"	3/4"	63,0	30,0	38,1
BW2310-10PA45	BW23.7043.1010	10	5/8"	5/8"	68,0	27,0	34,0
BW2312-12PA45	BW23.7043.1212	12	3/4"	3/4"	69,0	28,0	38,1
BW2312-16PA45	BW23.7043.1216	12	3/4"	1"	77,0	32,0	44,5
BW2316-16PA45	BW23.7043.1616	16	1"	1"	79,0	31,0	44,5
BW2316-20PA45	BW23.7043.1620	16	1"	1.1/4"	93,0	38,0	50,8
BW2320-20PA45	BW23.7043.2020	20	1.1/4"	1.1/4"	108,0	41,0	50,8
BW2320-24PA45	BW23.7043.2024	20	1.1/4"	1.1/2"	99,0	47,0	60,3
BW2324-24PA45	BW23.7043.2424	24	1.1/2"	1.1/2"	125,0	47,0	60,3
BW2324-32PA45	BW23.7043.2432	24	1.1/2"	2"	115,0	42,0	71,4
BW2332-32PA45	BW23.7043.3232	32	2"	2"	155,0	64,0	71,4

MATERIAL: Carbon Steel

FINISH: Chromium-(VI) Free plating / ROHS compliant

Suitable to be used on medium and high pressure braided and spiral hoses:

FORZA UNO R1AT/1SN; FORZA UNO "SHARK SKIN" R1AT/1SN; FORZA UNO TROPIC R1AT/1SN; FORZA DUE R2AT/2SN; FORZA DUE "SHARK SKIN" R2AT/2SN; FORZA DUE TROPIC R2AT/2SN; BALPAC PREMIUM R16/2SC; BALPAC PREMIUM "SHARK SKIN" R16/2SC; BALPAC PREMIUM TROPIC R16/2SC; IMPACTUS 5K; IMPACTUS 6K; BALPAC 3000 R17/1SC; BALPAC 3000 "SHARK SKIN" R17/1SC; 2-MAX JACK; BALWASH 1W; BALWASH 2W; BALMASTER BESTFLEX R12; BALMASTER BESTFLEX 4SP; POWERSPIR BESTFLEX 4SH; POWERSPIR BESTFLEX R13 (3/4" & 1"); POWERSPIR BESTFLEX R15 (3/4" & 1")