

BALFLEX D105 & D165 PORTABLE BENCH TOP CRIMPERS

D165

- 60 Ton
- 1.25" Max hose diameter 2 & 4 wire
- 1" Max hose diameter 6 wire (with DA Tool)
- Manual Crimping
- 1 HP
- 300 Crimps-per-hour (Approximate)

"D" Series Standard Die Sizes		
D100 Die Series	D200 Die Series	Effective Crimp Range
7mm	7mm	7-8mm
8mm	8mm	8-10mm
10mm	10mm	10-13mm
12mm	12mm	12-15mm
14mm	14mm	14-17mm
16mm	16mm	16-20mm
19mm	19mm	19-23mm
22mm	22mm	22-26mm
25mm	25mm	25-29mm
28mm	28mm	28-32mm
31mm	31mm	31-35mm
35mm	35mm	35-39mm
39mm	39mm	39-43mm
43mm	43mm	43-47mm
	47mm	47-51mm
	51mm	51-55mm
	54mm	54-58mm
	58mm	58-61mm



D105

- 35 Ton
- 1" Max hose diameter 2 wire
- .75" Max hose diameter 4 wire
- Manual Crimping
- 1 HP
- 450 Crimps-per-hour (Approximate)

"D" Series Die Notes

- D100 Die Series Crimp Length:
- 7- 9mm Crimp Dia: 25mm Crimp Length
- 10-22mm Crimp Dia: 44mm Crimp Length
- 25-43mm Crimp Dia: 57mm Crimp Length
- D200 Die Series Crimp Length 7-22mm Crimp Dia.: 51mm Crimp Length
- 25-38mm Crimp Dia.: 64mm Crimp Length
- 39-58mm Crimp Dia.: 76 mm Crimp Length

Special Die sizes and configurations are available

Construction characteristics and dimensions may be changed at anytime wthout prior notice

The data contained herin is for information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product.

Any use of the product not in conformance with the manfacturer's instruction may be dangerous

Only items in this catalog are carried in stock. Some items are subject to minimum quantities or sold in multiples of standard quantities. Please refer to the price list or contact our commercial department. Prices subject to change without notice.

Balflex[®] - The European Technology