



Balflex® SUPERJACK

The Best Name You Can Get In Hose

Balflex® SUPERJACK – 10.1046. - 2 steel braids

High pressure, double steel wire braid reinforced thermoplastic hydraulic hose



Inner tube:	seamless oil resistant thermoplastic
Reinforcement:	2 high tensile steel wire braid
Outer tube:	orange, oil and weather resistant polyurethane
Safety factor:	2.5: 1 on 1/4" hose and 2.1: 1 on 3/8" size
Application:	high pressure hydraulic systems, hydraulic jacks, rescue equipments, safety equipments, earthmoving equipments and mining equipments.
Temperature range:	- 40°C (- 40°F) + 100°C (+ 212°F) Max. temperature recommended for water base hydraulic fluids: + 65°C (+ 149°F)
Couplings:	Balflex® crimped fittings 23 serie

part number	Ø nom.	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
			mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
SJ-04	1/4"	- 4	6,3	0.25	14,1	0.56	700	10000	1750	25000	100	3.94	0,29
SJ-06	3/8"	- 6	9,5	0.38	17,5	0.69	700	10000	1500	21750	150	5.91	0,42

Construction characteristics and dimensions may be changed at anytime without prior notice

The data contained herein is for information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product.

Any use of the product not in conformance with the manufacturer's instruction may be dangerous

Only items in this catalog are carried in stock. Some items are subject to minimum quantities or sold in multiples of standard quantities. Please refer to the price list or contact our commercial department. Prices subject to change without notice.

Balflex® - The European Technology